



*Taking Sulfur Out of the Equation*

---

## Sorbent Specification

### SulfaTrap™-R2 Sulfur

---

SulfaTrap™ is a high-capacity, fast-reacting sorbent that effectively remove sulfides, mercaptans, tetrahydrothiophene (THT), di-sulfides and tri-sulfides, hydrogen sulfide (H<sub>2</sub>S) and carbonyl sulfide (COS) and reduce the sulfur concentration in the fuel to ppbv levels

**Intended Use:** Sulfur removal from gaseous flow streams, including natural gas and propane.

**Operating Conditions:** Ambient temperature up to 45°C. Preferred moisture content of less than 1000 ppmv in feed stream.

**General Specifications:**

**Size:** 1/16" pellets

**Appearance:** medium brown

**Bulk Density:** 35-40 lbs/ft<sup>3</sup>

**LOD (120°C):** <2 wt%

**Packaging:** Packaged in plastic bags and placed in steel or plastic drums.

---

Each production lot of SulfaTrap™-R6 will be delivered with a Certificate of Analysis including the following information:

Bulk Density

LOD (120°C)

Sulfur removal capacity

**Standard sorbent screening test:**

30,000 h<sup>-1</sup> GHSV, 50 ppmv each dimethyl sulfide and ethyl mercaptan, 19-23°C, 4000 ppmv moisture, natural gas blend

Sample drawn from 1L composite sample of 1.2 ft<sup>3</sup> lot

Minimum 2% combined sulfur loading by weight at breakthrough